

CERTIFICATE OF CONSTANCY OF PERFORMANCE

0905-CPR-202497-01

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation), this certificate applies to the construction product(s)

Product(s): Building hardware - Locks and latches - Mechanically operated locks, latches and locking plates (refer to attached appendix for details and conditions)

Placed on the market under the name or trademark of: Allegion Security Technologies (China) Co., Ltd.
Building 10, No. 8158, Tingwei Road, Jinshan Industry Park, Shanghai, 201506, China

and produced in the manufacturing plant(s): SG-15309

Intended use: When used with an appropriate door closing device on fire and/or smoke control doors to fulfil the self-closing requirement of such doors, and thereafter to ensure that the door remains shut.

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s):

EN 12209:2003/AC:2005

Under System 1 for the performance set out in this certificate are applied and that the performance of the construction product fulfils all the prescribed requirements for these performances.

This certificate was first issued on **2020-12-28** and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performances of the declared essential characteristics, do not change, and the construction product, and the manufacturing conditions in the plant are not modified significantly, unless suspended or withdrawn by the product certification body.

The issued document and statement(s) herein makes reference only to a presumption of conformity in accordance with the CPR Regulations EU 305/2011 (as amended). However, it is the manufacturer's or their authorised representative's sole responsibility to affix the CE logo and, by doing so, confirms full compliance and conformity to all other European mandatory directives and regulations that may also apply.



Signature:

[Handwritten signature]

Date: 2020-12-28

Name:

Dipl.-Ing. Roland Heine

Issue: 01

Position: Certification Manager



This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

Intertek Deutschland GmbH, Stangenstraße 1, 70771 Leinfelden-Echterdingen
Tel.: +49 711 27311-0 E-Mail: nb0905@intertek.com Web: www.intertek.de

CERTIFICATE OF CONSTANCY OF PERFORMANCE

0905-CPR-202497-01

APPENDIX TO: Certificate of Constancy of Performance

Brand: Briton

Model Ref: EL3020-b55, EL3020, EL3020-b80, EL3040-b55, EL3040, EL3010-b55, EL3010, EL3050-b55, EL3050, EL3030-b55, EL3030

Table A1. Product description for mechanically operated locks, latches and locking plates from Allegion Security Technologies (China) Co., Ltd.

Function	Model Number	Backset (mm)	C to C distance (mm)
Sash lock Handle only operate latch, cylinder operate latch and dead bolt.	EL3020-b55	55	72
	EL3020	60	72
	EL3020-b80	80	72
Passage latch Only latch bolt function, handle operate latch.	EL3040-b55	55	72
	EL3040	60	72
Deadlocking bolt Only deadbolt function, cylinder operate deadbolt.	EL3010-b55	55	72
	EL3010	60	72
Night latch Handle operate latch, cylinder operate latch.	EL3050-b55	55	72
	EL3050	60	72
Bathroom lock Latch is operated by handle, deadbolt is operated by turn.	EL3030-b55	55	78
	EL3030	60	78

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

Intertek Deutschland GmbH, Stangenstraße 1, 70771 Leinfelden-Echterdingen
Tel.: +49 711 27311-0 E-Mail: nb0905@intertek.com Web: www.intertek.de

CERTIFICATE OF CONSTANCY OF PERFORMANCE

0905-CPR-202497-01

APPENDIX TO: Certificate of Constancy of Performance

Table A2. Mechanical test reports & product classification for mechanically operated locks, latches and locking plates^{a, b} from Allegion Security Technologies (China) Co., Ltd.

Test Report	Model Number	Product Classification										
		3	X	9	1 ^b	0	G	3	B	C	2	0
160920013GZU-001 160920013GZU-002	EL3020-b55, EL3020, EL3020-b80	3	X	9	1 ^b	0	G	3	B	C	2	0
	EL3040-b55, EL3040	3	X	9	1 ^b	0	G	-	B	0	2	0
	EL3010-b55, EL3010	3	X	9	1 ^b	0	G	3	B	C	0	0
	EL3050-b55, EL3050	3	X	9	1 ^b	0	G	2	B	B	2	0
	EL3030-b55, EL3030	3	X	9	1 ^b	0	G	-	B	0	2	0

Table A3. Fire test report(s) for mechanically operated locks, latches and locking plates^a from Allegion Security Technologies (China) Co., Ltd.

Test Report	Model tested	Test Method	Fire Resistance (minutes)	
			Integrity (E)	Insulation (I)
171101005SHF-BP-1	EL3020-b80	EN 1634-1:2014	260	17
Test configuration: Single leaf single action swing steel fire door assembly Orientation: Open away the furnace.				
171101004SHF-BP-2	EL3020-b80	EN 1634-1:2014	111	111
Test configuration: Single leaf single action swing timber fire door assembly Orientation: Open into the furnace.				
Model numbers in Table A1 were assessed as having same performance.				

Notes.

- The lock and plate shall be installed in accordance with the installation instructions for the product(s).
- Digit 4 grade "1" was based on the test result from fire resistance test (refer to Table A3).

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

Intertek Deutschland GmbH, Stangenstraße 1, 70771 Leinfelden-Echterdingen
 Tel.: +49 711 27311-0 E-Mail: nb0905@intertek.com Web: www.intertek.de

CERTIFICATE OF CONSTANCY OF PERFORMANCE

0905-CPR-202497-01

APPENDIX TO: Certificate of Constancy of Performance

Table A4. Annex ZA Related Information for Mechanically operated locks, latches and locking plates from Allegion Security Technologies (China) Co., Ltd.

Product:	Mechanical locks and their strike plates		
Intended use:	On fire and smoke compartmentation doors (to fulfil the self-closing requirements of such doors)		
Requirement/ characteristic	Standard clause	Result Summary	
		For Latch lock: EL3020-b55, EL3020, EL3020-b80, EL3040-b55, EL3040, EL3050-b55, EL3050, EL3030-b55, EL3030	For deadlocking bolt: EL3010-b55, EL3010
Self-closing ability	Closing force (5.4.2)	Grade 9, Less than 15N	NPD (No Performance Determined)
	Return force of latch bolt (5.1.2)	Pass, More than 2.5 N	NPD
Durability of self-closing action	Durability of latch action (5.3.1)	Grade X 200 000 cycles	NPD
Ability to maintain door in closed position and not contribute to the spread of fire	Resistance to side load on latch bolt (5.2.1)	Grade 3 3kN	NPD
	Suitability for use on fire/smoke doors (5.5)	Pass Grade 1 (refer to Table A3)	
Control dangerous substances	Dangerous substances (5.1.1)	No dangerous substances declared for this product/ intended use	

END OF DOCUMENT

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

Intertek Deutschland GmbH, Stangenstraße 1, 70771 Leinfelden-Echterdingen
Tel.: +49 711 27311-0 E-Mail: nb0905@intertek.com Web: www.intertek.de